




Cumulus Automation Modules

Leslie Carr

- **Prototyping, integration and tools development**
- **Distributed team**



Barry Peddycord III
Raleigh Durham, US



Kristian Van Der Vliet
Bristol, UK



Leslie Carr
San Francisco, US

Former



Nat Morris
West Wales, UK



Stanley Karunditu
Raleigh Durham, US

- **Treat like your servers**
 - No need to use custom tools and expect scripts
- **Partner with your server system administrators**
 - Use what they are using and collaborate !
- **Unified Monitoring**
 - Use server tools and existing monitoring systems

▪ Ansible

- Agent-less (via SSH from mgmt host)
- No CL package required.



▪ Puppet

- Puppet agent & Facter in addons repo
- 3.6.2 (puppet as of CL2.5)
- Enterprise version also available (amd64 only)



▪ Chef

- amd64 & powerpc packages in addons repo
- 11.6.2 as of CL2.5



- **Unified automation modules**
 - Consistency across all toolsets - identical behaviour
 - Built for production use, not demo-ware
 - Easy to install via:
 - **Ansible Galaxy**
 - **Chef Supermarket**
 - **Puppet Forge**

- **Modules**
 - cl-license
 - cl-ports
 - cl-interfaces
 - cl-interface-policy

- **Background:**

- To enable switchd a license needs to be installed
- Normally an engineer would have to run “cl-license”

- **Behaviour:**

- Checks if license is installed and up to date.
- Checks expiration date. If license has not expired, then do nothing.
- Confirms the source parameter is of the correct format.
- Installs license if either license has expired or does not exist.



```
cumulus_license:  
  src: 'http://mgmtserver.corpnet.com/cumulus.lic'  
  force: true  
  notify: reload switchd
```



```
cumulus_license { 'license':  
  src => 'http://mgmtserver.corpnet.com/cumulus.lic',  
  force => true,  
  notify => service[switchd]  
}
```




```
cumulus_license 'corpnet' do  
  source 'http://mgmtserver.corpnet.com/cumulus.lic'  
  force true  
  notifies :reload, "service[networking]"  
end
```


■ Background:

- Switch port attributes are configurable
 - 4 x 10G ports combined (or ganged) into one 40G
 - 40G ports can be split (or unganged) into 4 x 10G
- Defined in /etc/cumulus/ports.conf

■ Behaviour:

- Write out /etc/cumulus/ports.conf replacing everything with the declared config
- Supports port ranges



ports.conf from a T+ 48x10G+4x40G

```
1=40G/4
2=40G/4
3=40G/4
4=40G/4
5=10G
6=10G
7=10G
```

4 x 10G
combined to 40G

...

```
45=10G
46=10G
47=10G
48=10G
49=40G
50=4x10G
```

40G broken out
to 4 x 10G

Automation tools overview - Modules - cl-ports



```
cumulus_ports:
  speed_40g_div_4: ["swp1-4"]
  speed_10g: ["swp5-48"]
  speed_4_by_10g: ["swp49-50"]
  speed_40g: ["swp51-52"]
notify: restart switchd
```



```
cumulus_ports { 'speeds':
  speed_40g_div_4 => ["swp1-4"],
  speed_10g => ["swp5-48"],
  speed_4_by_10g => ["swp49-50"],
  speed_40g => ["swp51-52"]
  notify => Service['switchd']
}
```



```
cumulus_ports 'speeds' do
  speed_40g_div_4 ["swp1-4"],
  speed_10g ["swp5-48"],
  speed_4_by_10g ["swp49-50"],
  speed_40g ["swp51-52"]
  notifies :restart, "service[switchd]"
end
```

- **Background:**

- Assumes interface config is stored in separate files under a directory.
- Doesn't support config merging. overwrites existing config.

- **Behaviour:**

- Module acts only on a single interface.
- Checks JSON formatted existing config and compares with generated JSON desired config
- Overwrites existing config using ifquery call, that converts desired JSON hash into regular text and copies to single interface text file.



```
cumulus_bridge: name=br0 ports="swp11-12 swp32-33 bond0"
                  alias_name="vlan aware bridge" mtu=9000 vlan_aware=true
                  vids="1-300" mstpctl_treeprio=4096

cumulus_bond: name=bond0 slaves="swp3-4" ipv4="10.1.1.1/24"

cumulus_interface: name=br0.1 ipv4="10.1.1.1/24"

cumulus_interface: name=swp33 speed=1000 alias_name="only has vlans1-10"
                   vids: "1-10"

cumulus_interface: name=lo addr_method='loopback'

cumulus_interface: name=eth0 addr_method='dhcp'
```



```
cumulus_bridge { 'br0':  
  ports => ['swp11-12', 'swp32-33', 'bond0'],  
  alias_name => 'vlan aware bridge',  
  mtu => '9000',  
  vids => ['1-300'],  
  vlan_aware => true,  
  mstpctl_treeprio => '4096'  
}  
cumulus_bond { 'bond0':  
  slaves => ['swp3-4'],  
  clag_id => 1  
}  
cumulus_interface { 'br0.1':  
  ipv4 => '10.1.1.1/24'  
}  
cumulus_interface { 'swp33':  
  speed => '1000'  
  alias_name => 'only has vlans 1-10'  
  vids => ['1-10']  
}  
cumulus_interface{ 'lo':  
  addr_method => 'loopback'  
}  
cumulus_interface{ 'eth0':  
  addr_method => 'dhcp'  
}
```

Automation tools overview - Modules - cl-interfaces



```
cumulus_bridge 'br10' do
  ports ['swp11-12', 'swp32-33', 'bond0']
  alias_name 'vlan aware bridge'
  vlan_aware true
  vids "1-300"
  mtu 9000
  mstpctl_treeprio 4096
end

cumulus_bond 'bond0' do
  slaves ['swp3-4']
end

cumulus_interface 'swp33' do
  ipv4 '10.30.1.1/24'
  speed 1000
  alias_name 'only has vlans 1-10'
end

cumulus_interface 'lo' do
  addr_method 'loopback'
end

cumulus_interface 'eth0' do
  addr_method 'dhcp'
end
```

- **Background:**
 - Enforcing which interfaces are configured on a switch
 - Stops rogue interfaces being setup ad-hoc
- **Behaviour:**
 - Assumes interface config distributed in individual files specific directory
 - Checks that interface files listed exists in enforcement list
 - Example: `'lo, eth0, swp1-10'` is the enforcement policy list
 - If interface directory has `"swp11"` file, it is deleted.





```
cl_interface_policy: allowed="lo eth0 swp1-33 br0 br0.1-10 bond0-10"  
notify: reload networking
```



```
cumulus_interface_policy { 'policy':  
  allowed => ['lo', 'eth0', 'swp1-33', 'br0', 'br0.1-10', 'bond0-10'],  
  notify => service['networking']  
}
```



```
cumulus_interface_policy 'policy' do  
  allowed ['lo', 'eth0', 'swp1-33', 'br0', 'br0.1-10', 'bond0-10']  
  notifies :reload, "service[networking]"  
end
```


- **Treat like your servers**
 - No need to use custom tools and expect scripts
- **Partner with your server system administrators**
 - Use what they are using and collaborate !
- **Unified Monitoring**
 - Use server tools and existing monitoring systems

Configuration management tool should be the source of truth

Scenario - switch needs replacing

- Remove old device
- Update MAC address in DHCPd on management server
- Clear any old certificates (Puppet/Chef)
- Install new device
- ONIE installs CL
- ZTP bootstraps automation tool
- Switch back in service

Only update required

```
host sw-rack-88-tor-2 {  
    hardware ethernet 00:11:22:33:44:55;  
    option host-name "sw-rack-88-tor-2";  
}
```

- **Foundations**
- **Automation tool overview**
- **Unified automation modules**
- **Ansible**
- **Puppet**
- **Chef**
- **Infrastructure testing**
- **Continuous integration**
- **Summary**

▪ Ansible

- Agent-less (via SSH from mgmt host)
- No CL package required.



▪ Puppet

- Puppet agent & Facter in addons repo
- 3.6.2 (puppet as of CL2.5)
- Enterprise version also available



▪ Chef

- amd64 & powerpc packages in addons repo
- 11.6.2 as of CL2.5



- **Salt**

- Agent-less deployment working
- PowerPC packages for agent not yet available (working with Salt team)
 - Dependency on ZeroMQ for PowerPC


- **CFEngine**

- Enterprise version working on Cumulus Linux
- Community PowerPC packages not available

- **Foundations**
- **Automation tool overview**
- **Unified automation modules**
- **Ansible**
- **Puppet**
- **Chef**
- **Infrastructure testing**
- **Continuous integration**
- **Summary**

- **Unified automation modules**
 - Consistency across all toolsets - identical behaviour
 - Built for production use, not demo-ware
 - Easy to install via:
 - **Ansible Galaxy**
 - **Chef Supermarket**
 - **Puppet Forge**

- **Modules**
 - cl-license
 - cl-ports
 - cl-interfaces
 - cl-interface-policy





Thank You!

© 2014 Cumulus Networks. Cumulus Networks, the Cumulus Networks Logo, and Cumulus Linux are trademarks or registered trademarks of Cumulus Networks, Inc. or its affiliates in the U.S. and other countries. Other names may be trademarks of their respective owners. The registered trademark Linux® is used pursuant to a sublicense from LMI, the exclusive licensee of Linus Torvalds, owner of the mark on a world-wide basis.